



International University of Africa



Deanship of Graduate Studies

Study of the Recycle and Reuse of Domestic Wastes

A Thesis Submitted in Partial Fulfillment of the Requirements for the
Degree of M.Sc. in Industrial Chemistry

by:

Aeisha Adam Osman Abdelkreem

B.Sc. (Industrial Chemistry) U.J

Supervisor:

Prof. Babiker Karama Abdalla

September 2016

Dedication

This thesis is dedicated to my parents at first and my family, whom there were motivated me all the time to see me successful and prepotent, by supporting and encouraged me invariably, Thanks a lot.

Acknowledgement

First and foremost, I thank God for the numerous blessings he has bestowed upon me throughout. Thanks to my supervisor Prof/ BabikerKramaAbdalla, for his advices and support. Thankful extended to Industrial researches and consultancy center (IRCC) / ahead of laboratories Mr. MdohamedHussein Ali andSalma Abdelkhalig, Thanksalot for my friend MohammedGummaElshafie for helping and encourage me.

Abstract

Due to the modern trend in the field of bio-energy and replace it as an alternative to non-renewable energy, this study comes to illuminate light on biofuel production process from the waste cooking oil and reducing the harmful impact by protecting the environment from emission resulting comes from the production and use of diesel oil such as (CO_2 , CO , H_2S), in addition to the added value of the oil. Ease of production and cheap raw materials.

It produced by using trans-esterification process by using methanol mixed with Potassium hydroxide as catalyst, and then the mixture added to the oil in the magnetic stirring for two hour at 60 C° . It was separated in separator funnel by gravity. Lastly, bio-fuel was collected from the top layer and washed with hot water to give high purity. The glycerin from the bottom as by-product.

Laboratory analysis for biodiesel was obtained some results, the flash point is 115 C° and this useful for storage and transportation without cooling or holding in specific containers and this reversal for flash point of diesel oil which it has flash point 60 C° lowers, it has viscosity 6 cp and density 0.88 g/cm^3 , in addition to the little amount of sulphated ash content which ensure the safety engine for a long time.

الخلاصة

نظراً للتوجهات الحديثة في مجال الطاقة الحيوية المتجددة وإحلالها كبديل للطاقة غير المتجددة تأتي هذه الدراسة لتتير الضوء على عملية إنتاج الوقود الحيوي من الزيت الراجع من الطعام لما له من أثر في حماية البيئة من إنبعاث الغازات الناتجة من عملية إنتاج وإستخدام الديزل البترولي مثل (CO , CO_2 , H_2S) بالإضافة الي القيمة المضافة للزيت الراجع ، كما يفضل إستخدامه كبديل للديزل البترولي لسهولة إنتاجه ومن مواد خام مهمة وغير مكلفة لضررها البالغ بالبيئة.

تم إستخدام عملية الأسترة (Trans-esterification Process) في إنتاج الوقود الحيوي باستخدام الميثانول المخلوط مع هيدروكسيد البوتاسيوم المستخدم كعامل حفاز ثم يضاف الخليط إلى الزيت في الخلاط المغنطيسي عند درجة حرارة ٦٠ م° لمدة ساعتين وبعد ذلك يتم الفصل في القمع الزجاجي لنتحصل على الوقود الحيوي في الجزء الاعلى والجلسرين في الاسفل كنتاج ثانوي كما أن الفصل يعتمد على الجاذبية ، للحصول على نقاوة عالية من الديزل الحيوي يتم غسله بالماء الدافئ على عدة مراحل حتى نتحصل على طبقة نقية من الماء في الاسفل.

حللت عينات في المختبر و تم الحصول علي نتائج منها درجة اشتعال عالية تساوي (١١٥)م° وهذا يجعل ترحيله و تخزينه سهل من غير تبريد على عكس الديزل البترولي لان درجة حرارة اشتعاله قليلة (٦٠)م° ، كما وجدت درجة لزوجته (٦)س ب ، وكثافته (٠.٨٨) جم/سم^٣ بالإضافة الى انه يحتوى على كمية رماد (Sulphated Ash) بسيطة جدا مما يضمن سلامة المحرك لفترة اطول.

List of Contents

Title	Page No
Dedication	I
Acknowledgment	II
English Abstract	III
Arabic Abstract	IV
List of Content	V
List of Table	VII
List of Figure	VIII
Chapter One: Introduction	
1.1 Introduction	1
1.2 Objective	5
Chapter One: Literature review	
2-1 Background	7
2-2 Classification of waste	7
2-3 Contamination from Agricultural Wastes	7
2-4 Contamination from Industrial Wastes	9
2-5 Remediation and Rehabilitation of Soils Contaminated by Heavy Metals	9
2-6 Liquid Waste	11
2-6-1 Used Cooking Oil	11
2-6-2 Environmental problems for disposing used cooking oil	12
2-6-3 The Different Techniques to Produce Biodiesel	13
2-6-4 Biodiesels	13
2-6-4-1 Safety for Trans-esterification process	15
2-6-4-2 Physical Properties of Biodiesel	16
2-6-4-3 Six Factors Affecting Biodiesel Production	17
2-6-4-4 Storage Stability	17
2-6-4-5 Flash point	18
2-6-4-6 Density	18
Chapter Three: Materials and Methods	
3-1 Collection of oil materials	21
3-2 Preparation of the raw material	21
3-3 Processing in Biodiesel	21
3-3-1 Esterification	21

3-3-2 Separation 1	22
3-3-3 Mixing of Alcohol and Catalyst	22
3-3-4 Transesterification	22
3-3-5 Separation 2	23
3-3-6 Alcohol Removal	23
3-3-7 Washing	24
3.3.8 Total Biodiesel Produced Percentage	24
3-3-9 Reagent used	25
3-4 Chemical Properties Tests	25
3-4-1 Acid value	25
3-4-2 Peroxide value	26
3-4-3 Iodine value	26
3-4-4 Saponification value	27
3-4-5 Moisture content	28
3-4-6 Sulfured ash	29
3-5 Physical Properties Tests	30
3-5-1 Flash Point	30
3-5-2 Distillation of Biodiesel Products at Reduced Pressure 1	31
3-5-3 Density	32
3-5-4 API Gravity (American Petroleum Institute) Equation	33
3-5-5 Calculated Cetane Index by Four Variable Equation	33
3-5-6 Calculated Cetane Index by Iodine and Saponification Values	34
Chapter Four: Results and Discussion	
4.1 Results	36
4.2 Discussion:	39
Chapter Five: Conclusion and Recommendations	
4.3 Conclusion	42
4.4 Recommendations	43
References	44

List of Tables

Table No	Title	Page No
1	result analysis for Oil tests	36
2	result analysis for Biodiesel tests	37

List of Figures

Figure No	Title	Page No
1	The Chemical Reaction of Biodiesel Production by Transesterification	14
2	Stages of the Transesterification Reaction to Producing the Biodiesel	15
3	Waste cooking oil	51
4	Biodiesel and Glycerin comes from Transesterification Process in separation form	51
5	Biodiesel in first step of washing	51
6	Biodiesel in last step of washing	51
7	In the left Biodiesel after washing, and in the right Biodiesel and Glycerin before separation	52
8	Biodiesel in pure form	52
9	IR OF Biodiesel	38